

EL HYD OIL 68

DESCRIPTION:

EL Hydraulic Oil 68 was developed as an economical, general purpose anti-wear, rust, corrosion and oxidation inhibited oil. **EL Hydraulic Oil 68** is suitable for use where service requirements are normal to moderate and long-term heavy-duty protection is not critical. **EL Hydraulic Oil 68** has a dielectric strength above 35kV and is non-conductive.

FEATURES/BENEFITS:

- Good anti-foam protection
- Economical for older leaky systems
- Great rust and corrosion protection

APPLICATIONS:

EL Hydraulic Oil 68 is recommended for use in hydraulic systems utilizing radial or axial piston, vane, gear and other type pumps, where quality anti-wear hydraulic oil is required.

* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

TYPICAL TEST DATA

ISO GRADE	68
Specific Gravity @ 60 °F	0.9070
Viscosity, Kinematic cSt at 40°C, Min/Max	61.2 – 74.8
Viscosity, Kinematic cSt at 100°C	7.6
Viscosity Index	63
Flash Point, °F	345
Pour Point, °C (°F)	-36 (-33)
Color, Max	4.0
Zinc, wt%	0.02

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.