

Global ATF - Technical Data Sheet

DESCRIPTION:

Full Synthetic Global ATF is a full synthetic premium fluid designed for automatic transmissions of all North American, European, and Asian passenger car and commercial vehicles. Full Synthetic Global ATF provides exceptional oxidation, wear, frictional stability, sludge and deposit prevention, and anti-shudder properties required in today's high performance transmissions. It is also designed to deliver premium performance in older transmissions.

APPLICATIONS:

Full Synthetic Global ATF high viscosity automatic transmission fluid is suitable for use in Ford, GM, Toyota, and many other OEM applications.

Not recommended for use where Ford Type F/G, DCTs, and CVTs fluid is required.

- See table below for Specific Manufacturer's Applications

* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

Specific Gravity @ 60° F	.8495
Viscosity, Kinematic cSt at 40° C	30.2
Viscosity, Kinematic cSt at 100° C	7.0
Viscosity Index	208
Viscosity, Brookfield cP at -40°C	8,376
Flash Point, °F	360
Pour Point, °C (°F)	-54 (-65)
Color	RED

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.

Suitable for all Claims:
Aisin Warner AW-1
Allison C-4
Allison TES-295
Allison TES-389, TES-389B
Audi G 052 162, G 052 990, G 055 025
Audi G 055 005, G 055 162, G 052 540
BMW 7045E, BMW 8072B, LA 2634, LT 71141
BMW 83 22 0 142 516
Chrysler MS-10838 P/N 05142893AA
Chrysler MS-1872, MS-5931, P/N 04883077, MS 9602
DSIH 6p805 (Geely, Ssangyong, Mahindra 6sp)
Ford M
Ford M2C195-A
Ford Part # XL-12
GM AutoTrak II
GM P/N 12345866 (GM 9985835)
GM P/N 89021184, P/N 1052884 (GM 9985010)
GM-IID, IIIG, IIIH
Honda ATF Z-1
Honda DW-1
Hyundai NWS-9638
Hyundai/KIA PSF-3
Hyundai/Kia SP-II, SP-III, JWS 3314, JWS 3317
Hyundai/Kia SP-IV, SPH-IV, SP-IV RR
IdemitsuK17 (JATCO)
JASO 1-A
JASO 1-A-LV
JWS 3309 (Aisin Warner)
JWS 3324
Kia Red-1
MAN 339 Type Z-1
MAN 339F, 339 Type V-1
Mazda ATF-M III, ATF-MV

Mercedes GL-450 (ATF 3403)
Mercedes-Benz 236.1, 236.2, 236.3, 236.6, 236.7, 236.9, 236.11, 236.81
Mercedes-Benz 236.12, 236.14, 236.15
Mercedes-Benz 236.3 (P/N 000 989 88 03)
Mercedes-Benz 236.41
Mercedes-Benz 236.91
Mercedes-Benz; MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.9, 236.10 (NAG/Shell 3403), 236.11, 236.81
Mitsubishi ATF-J3, ATF-PA
Mitsubishi PS Fluid, Diamond SP-III
Mitsubishi SP-II, SP-III, DlaqueenATF J2
Mitsubishi SP-IV
Nissan 402, Nissan Matic-D, J, K
Nissan MaticS, MaticW
Nissan PSF-II
North American Models (Dexron VI, Mercon LV)
Other North American high viscosity ATF (Mercon V, ATF +4)
PSA AL-4
Renault DP-0
Saab 93 165 147
Saab P/N 45 30 09 800
Subaru ATF. ATF-HP
Subaru P/N K0209A0080
Suzuki 3314, 3317
Texaco N402 (JATCO), ETL-7045E (BMW 7045E), ETL-8072B (BMW 5 Sp)
Toyota PSF Type EH P/N 008886-01
Toyota T, T-II, T-III, T-IV
Toyota WS (JWS 3324)
VoithH55.6335
Volvo 4Speed (P/N 1161621)
Volvo 5/6 Speed (P/N 1161540/1161640)
Volvo 6 Speed MY 2011-2013 (P/N 31256774 or 31256675)
Volvo 97340, 97341
VW G 052 162, G 052 990, G 055 025
VW G 052 540, G 055 005, G 055 162

ZF 6 Speed (S671 090 255)
ZF TE-ML 03D, 04D, 05L, 16L, 17C
ZF TE-ML 09
ZF TE-ML 11 (3.4.5 speed)
ZF TE-ML 14A
ZF TE-ML 21L

*ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT